

StarLine Homes

Single Wide Standard Specifications & Options

GENERAL

- HUD Code
- 20 lb. Roof Load Std., 30 psf optional
- Thermal Zone 1 Std., zones 2 and 3 optional
- Wind Zone 1 Std., zones 2 and 3 optional

FRAME

- I - Beam: 12" or 10" model specific
- Outriggers: 95" spacing
- Crossmembers: 95" spacing
- Header: (Front/Rear) Flush, not recessed
- Axles: Spread (no equalizers) overslung mounted
- Brake Axles: One, except where more are mandatory by state DOT
- Hitch Beam: 8" Detachable Hitch

FLOOR

- Joists: 2x6 / 19.2" o.c.
- Carpet: Factory Select
- Carpet Bar: None
- Pad: 3.5 lb. (minimum) Rebond Pad
- Vinyl: Factory Select
- Decking: 19/32" 4x8 OSB T&G

EXTERIOR (7'-0" SIDEWALLS, 7'-0" ENDWALLS)

- Vinyl Siding: Standard
- Sheathing: WZ 1 - Foam standard, plant specific brand. WZ 2 & 3 - Includes OSB
- House Wrap: Over OSB (where used)
- Shutters: None

WINDOWS AND DOORS

- Front door: Out swing 34" x 76" blank, no storm
- Rear door: Out swing 34" x 76" blank, no storm
- Interior doors: Factory Select
- Windows: Metal single glaze, size per prints
Metal storm windows for thermal zone 2 and 3 only

ROOF / CEILING

- Design Load: 20 psf Live load standard, 30 psf options where needed
- Shingles: 20 year
- Trusses: 24" o.c. spacing
- Sheathing: 7/16" OSB
- Insulation: Blown Cellulose
- Ceiling: Textured
- Ceiling Slope: Vault/Flat Ceiling
- Attic Ventilation: Pot vents (low), Ridge vent high

PLUMBING

- Water Heater: 30 gallon electric
- Kitchen Sink: Stainless Steel, dbl bowl
- Lavatory Sinks: Plastic
- Faucets: Plastic
- Master Bath: 54 ABS Plastic Tub
- Hall Bath: 54 ABS Plastic Tub
- Main Water Shut Off

HVAC

- Heat: Electric (gas optional)
- Ductwork: Metal duct
- Thermostat: 8 Wire

ELECTRICAL

- Load Center: 200 amp
(100 amp allowed when gas option ordered – gas range and gas furnace)
- Exterior Receptacles and Switches: (1) GFI recept and cover
- Interior Receptacles and Switches: White, self contained
- Phone Jack(s): None
- AC: Conduit

WALLS

- Exterior Wall Construction: 2x4, 16" O.C. spacing
- Ext. Wall Height Sidewall 7'-0", Endwall 7'-0"
(combo vault/flat ceiling, per prints)
- Interior Wall Construction: 2x3, 24" O.C. spacing
- Wall Coverings: 3/8" minimum VOG or paper on gyp
- Wall Coverage at Closets: 3/8" gyp, raw

INTERIOR FEATURES

- Cabinets: MDF / 24" tall overheads
- Countertops (All): Formica
- Backsplash: None
- Closet Shelving: Closet Maid – vinyl wrapped metal
- Utility Shelving: None
- Refrigerator: 18 CF
- Range: Electric
- Range Hood: 30", 100 cfm min, vent through sidewall
- Valance on LR windows only. No mini blinds

COLOR SCHEME - Factory Select

THERMAL (INSULATION AND WINDOW SPECS)

- Zone I (standard) Windows: Metal (mil finish), single pane (no storm),
Floor: R-11 Wall: R-11 Roof: R-11
- Zone II (optional) Windows: Metal (mil finish) single pane w/ storm,
Floor: R-11 Wall: R-11 Roof: R-14
- Zone III (optional) Windows: Metal (mil finish) single pane w/ storm,
Floor: R-22 Wall: R-11 Roof: R-28

OPTIONS AVAILABLE

1. Dishwasher (\$450)
2. House Type Front Door w/ storm (\$225)
3. House Type Rear Door w/ storm (\$225)
4. Wire & Brace for Ceiling Fan, LR only (\$50)
5. Thermal Zone II (\$255)
6. Thermal Zone III (\$635)
7. Wind Zone II, includes OSB (\$1,150)
8. Wind Zone III, includes OSB and 16" O.C. Trusses (\$1,995)
9. Thermal Pane dual glaze Vinyl Windows (available for Thermal Zone 3 only) (\$160)
10. Ice Dam Protection (\$125)
11. Gas Option: Range and Furnace 100 amp (\$550) and 200 amp (\$599)
12. 30# roof load, 16" O.C. Trusses (\$495)
13. OSB Wrap (\$895)
14. 2x6 Sidewalls w/R-19 (\$599)
15. Recessed Header - 4" (\$75)
16. Shutters (Front Door Side & Hitch End) (\$75)